


YJ Planar Fast Recovery Diode Die Specification

200V 10A, Fast recovery diode die based on silicon planar process
Part No.: FRD10A200AS-290A

Main Products Characteristics

- Average forward current: $I_{F(AV)} = 10A$
- Maximum operating junction temperature: $T_J = 150\text{ }^\circ\text{C}$
- Planar Construction
- Top metal: Al



Maximum Ratings

Parameter	Symbol	Rating
Repetitive peak reverse voltage	V_{RRM}	200V
Average forward current	$I_{F(AV)}$	10A
Non-repetitive peak surge current ($t_p = 8.3\text{ ms}$, halfwave, 1 cycle)	I_{FSM}	120A
Storage temperature range	T_{stg}	-40 to +150 $^\circ\text{C}$
Maximum operating junction temperature	T_J	150 $^\circ\text{C}$

Static Electrical Characteristics ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	
		Spec	Typical
Reverse breakdown voltage $I_R = 50\mu\text{A}$	V_{BR}	220V	230V
Maximum forward voltage drop $I_F = 10A$, Pulse Test: $t_p = 380\text{ }\mu\text{s}$, $\delta \leq 2\%$	V_F	1.0V	0.9V
Reverse Recovery Time $I_F = 0.5A$, $I_R = 1A$, $I_{rr} = 0.25A$	T_{rr}	35ns	28ns
Maximum reverse current $V_R = V_{RRM}$ Pulse Test: $t_p = 10\text{ ms}$, $\delta \leq 2\%$	I_R	2 μA	0.02 μA

Device Schematics and Outline Drawing

Die Thickness	290 μm
Die Size *	2540X2540 μm
Top Metal Pad	2280X2280 μm
Active Area	2220X2220 μm
Top Metal	Al
Back Metal	Ag

Note: 1 *: Cutting street width is around 40 μm

Important Notice

Specification apply to die only. Actual performance may degrade when assembled.

Yangjie Electronics does not guarantee device performance after assembly.
All operating parameters must be validated for each customer application by customer's technical experts.

Data sheet information is subjected to change without notice.

Recommended Storage Environment:

Store in original container, in dessicated nitrogen, with no contamination.

Shelf life for parts stored in above condition is 2 years.

If the storage is done in normal atmosphere shelf life is reduced to 6 months.